

# PRODUCT DATASHEET

## WALL PACK SLIM 30W 120-347V D 8 3CCT BZ D

WALL PACK SLIM DUAL SELECTABLE | Slim Wall Pack with selectable CCT and wattage



### Areas of application

- Schools
- Warehouses
- Municipal buildings
- Commercial buildings

### Product features

- Selectable CCT: 3000 K, 4000 K and 5000 K
- Selectable wattage and lumen output
- Adjustable up to 90 degrees
- Up to 140 LPW
- CRI > 80
- DLC Premium: assures high energy efficient & eligible for utility rebates

## TECHNICAL DATA

### Additional product data

|                              |                                                                                                              |
|------------------------------|--------------------------------------------------------------------------------------------------------------|
| Ordering Abbreviation        | SLMWPKC3A/S030UNHD8SC2/BZ/D                                                                                  |
| Abbrev. With Packaging Info. | SLMWPKC3AS030UNHD8SC2BZD 1/CS 1/SKU                                                                          |
| NAED                         | 63071                                                                                                        |
| Family Brand Name            | PERFORMANCE CLASS™                                                                                           |
| General Description          | SLIM WALL PACK 3A, SELECTABLE 10/20/30, 120-347V, 0-10V DIM, 3000/4000/5000K, BRONZE, DAYLIGHT/MOTION SENSOR |
| Warranty                     | 5 years                                                                                                      |

### Electrical data

|                           |                     |
|---------------------------|---------------------|
| Nominal Wattage           | 10.00/20.00/30.00 W |
| Nominal voltage           | 120.00...347.00 V   |
| Power factor              | ≥ 0.90              |
| Total Harmonic Distortion | < 20 %              |

### Photometrical data

|                             |                   |
|-----------------------------|-------------------|
| Lumens                      | 1400/2800/4200 lm |
| Efficacy                    | 140 lm/W          |
| Color Temperature/CCT       | 3000/4000/5000 K  |
| Color Rendering Index (CRI) | > 80              |
| Luminaire Type              | Wall pack         |

### Dimensions & Weight

|                |         |
|----------------|---------|
| Length         | 7.28 in |
| Width          | 7.8 in  |
| Height         | 4.92 in |
| Product weight | 5.92 lb |

### Materials & Colors

|                  |          |
|------------------|----------|
| Luminaire Finish | Bronze   |
| Housing color    | Bronze   |
| Housing          | Aluminum |
| Mercury content  | 0.0 mg   |

### Application & Mounting

|                               |             |
|-------------------------------|-------------|
| Ambient temperature range     | -40...40 °C |
| Maximum Operating Temperature | 104 °F      |
| Minimum Operating Temperature | -40 °F      |
| Dimming                       | Yes         |

|                          |         |
|--------------------------|---------|
| Type of Dimming          | 0-10V   |
| Mounting                 | Surface |
| Indoor/Outdoor           | Outdoor |
| Replaceable light source | No      |
| Primary Lamp Type        | SMD     |

### Lifespan

|                         |       |
|-------------------------|-------|
| Average Rated Life (hr) | 50000 |
|-------------------------|-------|

### Logistical data

|                   |       |
|-------------------|-------|
| Case Qty          | 1     |
| Case Length (in)  | 8.661 |
| Case Width (in)   | 7.874 |
| Case Depth (in)   | 5.906 |
| Case Cube (ft)    | 0.233 |
| Case Weight (lbs) | 6.493 |
| Pallet Qty        | 200   |

### Certificates & Standards

|                                  |                    |
|----------------------------------|--------------------|
| Certification Listing            | RoHS / cULus / FCC |
| Replaceable light source (EPREL) | Not replaceable    |

### Optional accessories

| Product image                                                                       | Product name                                | UPC     |
|-------------------------------------------------------------------------------------|---------------------------------------------|---------|
|  | Standalone Commissioning Remote SLIM WLPK2A | OS62298 |

### DOWNLOAD DATA

| Spec Sheets and Product Documents                                                  |                           | Document name                            |
|------------------------------------------------------------------------------------|---------------------------|------------------------------------------|
|  | Product Family Spec Sheet | DUAL SELECTABLE SLIM WALL PACK LEDLUM169 |
|  | Product Family Spec Sheet | DUAL SELECTABLE SLIM WALL PACK           |
|  | Product Family Spec Sheet | SLIM WALL PACK                           |
|  | Product Family Spec Sheet | SLIM WALL PACK                           |

| Photometric and lighting design files                                             |                | Document name              |
|-----------------------------------------------------------------------------------|----------------|----------------------------|
|  | IES file (IES) | SLIM WALLPACK 3A IES FILES |

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.