

PRODUCT DATASHEET

WALL PACK SLIM 30W 120-347V D 8 3CCT WH P

WALL PACK SLIM DUAL SELECTABLE | Slim Wall Pack with selectable CCT and wattage



Areas of application

- Schools
- Warehouses
- Municipal buildings
- Commercial buildings

Product features

- Selectable CCT: 3000 K, 4000 K and 5000 K
- Selectable wattage and lumen output
- Adjustable up to 90 degrees
- Up to 140 LPW
- CRI > 80
- DLC Premium: assures high energy efficient & eligible for utility rebates

TECHNICAL DATA

Additional product data

Ordering Abbreviation	SLMWPKC3A/S030UNHD8SC2/WHP
Abbrev. With Packaging Info.	SLMWPKC3AS030UNHD8SC2WHP 1/CS 1/SKU
NAED	63840
Family Brand Name	PERFORMANCE CLASS™
General Description	SLIM WALLPACK 3A, SELECTABLE WATTAGE 10/20/30W, 120-347V, 0-10V DIMMING, 80 CRI, SELECTABLE CCT 3000/4000/5000K, WHITE, PHOTOCELL
Warranty	5 years

Electrical data

Nominal Wattage	10.00/20.00/30.00 W
Nominal voltage	120.00...347.00 V
Power factor	≥0.90
Total Harmonic Distortion	< 20 %

Photometrical data

Lumens	1400/2800/4200 lm
Efficacy	140 lm/W
Color Temperature/CCT	3000/4000/5000 K
Color Rendering Index (CRI)	> 80
Luminaire Type	Wall pack

Dimensions & Weight

Length	7.28 in
Width	7.8 in
Height	4.9 in
Product weight	5.92 lb

Materials & Colors

Luminaire Finish	White
Housing color	White
Housing	Aluminum
Mercury content	0.0 mg

Application & Mounting

Ambient temperature range	-40...+40 °C
Maximum Operating Temperature	104 °F
Minimum Operating Temperature	-40 °F

Dimming	Yes
Type of Dimming	0-10V
Mounting	Surface
Indoor/Outdoor	Outdoor
Replaceable light source	No
Primary Lamp Type	SMD

Lifespan

Average Rated Life (hr)	100000
-------------------------	--------

Logistical data

Case Qty	1
Case Length (in)	8.661
Case Width (in)	7.874
Case Depth (in)	5.906
Case Cube (ft)	0.233
Case Weight (lbs)	6.493
Pallet Qty	200

Certificates & Standards

Certification Listing	RoHS / FCC / cULus
Replaceable light source (EPREL)	Not replaceable

Optional accessories

Product image	Product name	UPC
	Standalone Commissioning Remote SLIM WLPACKN2A	OS62298

DOWNLOAD DATA

Spec Sheets and Product Documents		Document name
	Installation Guide	Dual Selectable Slim Wallpack Installation Manual
	Product Family Spec Sheet	DUAL SELECTABLE SLIM WALL PACK LEDLUM169
Photometric and lighting design files		Document name
	IES file (IES)	SLIM WALLPACK 3A IES FILES

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.