

PRODUCT DATASHEET

VAPOR S025 UNH D 8 SC7 24 GR E

Vapor Tight Dual Selectable | Vapor Tight with selectable CCT and wattage



Areas of application

- Manufacturing facilities
- Agricultural buildings
- Warehouses
- Canopies and loading docks
- Parking garages

Product features

- Selectable wattage and lumen output
- Selectable CCTs: 3500/4000/5000K
- Up to 144 LPW
- Optional integrated motion/daylight sensor and/or emergency battery backup
- NSF Splash zone
- DLC
- Stainless steel clips and mounting brackets
- 120-347V
- Narrow body width

TECHNICAL DATA

Additional product data

Ordering Abbreviation	VAPOR3A/S025UNHD8SC7/24/GR/E
Abbrev. With Packaging Info.	VAPOR3AS025UNHD8SC724GRE 6/CS 1/SKU
SKU UPC	0046135624919
NAED	62491
General Description	Vapor Tight 3A, IP66, 15/20/25W selectable, 120-347V, 0-10V dimming, 3500/4000/5000K selectable, 2 foot, gray polycarbonate body, emergency back-up battery
Warranty	5 years

Electrical data

Nominal Wattage	15.00/20.00/25.00 W
Nominal voltage	120.00...347.00 V
Power factor	≥0.90
Total Harmonic Distortion	< 20 %

Photometrical data

Lumens	2160/2880/3600 lm
Efficacy	138 lm/W
Color Temperature/CCT	3500/4000/5000 K
Color Rendering Index (CRI)	> 80
Luminaire Type	Vapor-tight

Dimensions & Weight

Length	26.22 in
Width	3.23 in
Height	3.35 in
Product weight	3.44 lb

Materials & Colors

Luminaire Finish	Gray
Housing color	Gray
Housing	Polycarbonate (PC)
Mercury content	0.0 mg

Application & Mounting

Ambient temperature range	0...+40 °C
Maximum Operating Temperature	104 °F
Minimum Operating Temperature	0 °C

Dimming	Yes
Type of Dimming	0-10V
Mounting	Surface
Indoor/Outdoor	Indoor
Replaceable light source	No

Lifespan

Average Rated Life (hr)	100000
-------------------------	--------

BATTERY

Lithium Ion Battery	Li ion battery
Battery size [GMS]	Others

Logistical data

SKU Qty	1
Case Qty	6
Case Length (in)	28.622
Case Width (in)	7.992
Case Depth (in)	12.047
Case Cube (ft)	1.595
Case Weight (lbs)	25.172
SKU UPC	0046135624919
Pallet Qty	126

Certificates & Standards

Certification Listing	RoHS / FCC / cULus
Replaceable light source (EPREL)	Not replaceable

Optional accessories

Product image	Product name	UPC
	VAPOR 3A LENS 4'	OS62616
	VAPOR 3A CLIPS	OS62618
	VAPOR 3A MOUNTING KIT	OS62619

Product image	Product name	UPC
	VAPOR 3A CLIPS 8'	OS66345
	Standalone Commissioning Remote REMOTE CONTROL	OS60105

EQUIPMENT / ACCESSORIES

- Stainless Steel mounting brackets and V-hooks

DOWNLOAD DATA

Spec Sheets and Product Documents		Document name
	Installation Guide	UltraLED Vapor Tight 3A Installation Guide
	Product Family Spec Sheet	UltraLED™ Dual Selectable Vapor Tight 3A

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.