

PRODUCT DATASHEET

VAPOR S050 UNH D 8 SC7 48 GR E

Vapor Tight Dual Selectable | Vapor Tight with selectable CCT and wattage



Areas of application

- Manufacturing facilities
- Agricultural buildings
- Warehouses
- Canopies and loading docks
- Parking garages

Product features

- Selectable wattage and lumen output
- Selectable CCTs: 3500/4000/5000K
- Up to 144 LPW
- Optional integrated motion/daylight sensor and/or emergency battery backup
- NSF Splash zone
- DLC
- Stainless steel clips and mounting brackets
- 120-347V
- Narrow body width

TECHNICAL DATA

Additional product data

Ordering Abbreviation	VAPOR3A/S050UNHD8SC7/48/GRE
Abbrev. With Packaging Info.	VAPOR3AS050UNHD8SC748GRE 6/CS 1/SKU
SKU UPC	0046135624926
NAED	62492
Family Brand Name	Value Class
General Description	VAPOR TIGHT 3A, WATTAGE SELECTABLE 30/40/50, 120-347V, 0-10V DIM, 80 CRI, CCT SELECTABLE 3500/4000/5000K, 4 FOOT, GRAY, EMERGENCY BACK UP BATTERY
Warranty	5 years

Electrical data

Nominal Wattage	30.00/40.00/50.00 W
Nominal voltage	120.00...347.00 V
Power factor	≥0.90
Total Harmonic Distortion	< 20 %

Photometrical data

Lumens	4320/5760/7200 lm
Efficacy	138 lm/W
Color Temperature/CCT	3500/4000/5000 K
Color Rendering Index (CRI)	> 80
Luminaire Type	Vapor-tight

Dimensions & Weight

Length	49.21 in
Width	3.23 in
Height	3.35 in
Product weight	5.25 lb

Materials & Colors

Luminaire Finish	Gray
Housing color	Gray
Housing	Polycarbonate (PC)
Mercury content	0.0 mg

Application & Mounting

Ambient temperature range	0...+40 °C
Maximum Operating Temperature	104 °F

Minimum Operating Temperature	0 °C
Dimming	Yes
Type of Dimming	0-10V
Mounting	Surface
Indoor/Outdoor	Indoor
Replaceable light source	No

Lifespan

Average Rated Life (hr)	100000
-------------------------	--------

BATTERY

Lithium Ion Battery	Li ion battery
Battery size [GMS]	Others


Logistical data

SKU Qty	1
Case Qty	6
Case Length (in)	52.480
Case Width (in)	7.992
Case Depth (in)	12.047
Case Cube (ft)	2.924
Case Weight (lbs)	39.019
SKU UPC	0046135624926
Pallet Qty	90

Certificates & Standards

Certification Listing	RoHS / FCC / cULus
Replaceable light source (EPREL)	Not replaceable

Optional accessories

Product image	Product name	UPC
	VAPOR 3A LENS 4'	OS62616
	VAPOR 3A CLIPS	OS62618

Product image	Product name	UPC
	VAPOR 3A MOUNTING KIT	OS62619
	VAPOR 3A CLIPS 8'	OS66345
	Standalone Comissioning Remote REMOTE CONTROL	OS60105

EQUIPMENT / ACCESSORIES

- Stainless Steel mounting brackets and V-hooks

DOWNLOAD DATA

Spec Sheets and Product Documents		Document name
	Installation Guide	UltraLED Vapor Tight 3A Installation Guide
	Product Family Spec Sheet	UltraLED™ Dual Selectable Vapor Tight 3A

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.