

PRODUCT DATASHEET

VAPOR S090 UNH D 8 SC7 96 GR 6C

Vapor Tight Dual Selectable | Vapor Tight with selectable CCT and wattage



Areas of application

- Manufacturing facilities
- Agricultural buildings
- Warehouses
- Canopies and loading docks
- Parking garages

Product features

- Selectable wattage and lumen output
- Selectable CCTs: 3500/4000/5000K
- Up to 144 LPW
- Optional integrated motion/daylight sensor and/or emergency battery backup
- NSF Splash zone
- DLC
- Stainless steel clips and mounting brackets
- 120-347V
- Narrow body width

TECHNICAL DATA

Additional product data

Ordering Abbreviation	VAPOR3AS090UNHD8SC796GR6C
Abbrev. With Packaging Info.	VAPOR3AS090UNHD8SC796GR6C 1/CS 1/SKU
NAED	63581
General Description	VAPOR TIGHT 3A, IP66 SELECTABLE WATTAGE 70/80/90, 120-347V, 0-10V DIMMING, 80 CRI, SELECTABLE CCT 3500/4000/5000, 8', gray polycarbonate body, 6ft cord
Warranty	5 years

Electrical data

Nominal Wattage	70.00/80.00/90.00 W
Nominal voltage	120.00...347.00 V
Power factor	≥0.90
Total Harmonic Distortion	< 20 %

Photometrical data

Lumens	10080/11520/12960 lm
Efficacy	144 lm/W
Color Temperature/CCT	3500/4000/5000 K
Color Rendering Index (CRI)	> 80
Luminaire Type	Vapor-tight

Dimensions & Weight

Length	98.43 in
Width	5.31 in
Height	3.54 in
Product weight	13.01 lb

Materials & Colors

Luminaire Finish	Gray
Housing color	Gray
Housing	Polycarbonate (PC)
Mercury content	0.0 mg

Application & Mounting

Ambient temperature range	-40...+45 °C
Maximum Operating Temperature	113 °F
Minimum Operating Temperature	-40 °F
Dimming	Yes

Type of Dimming	0-10V
Mounting	Surface
Replaceable light source	No

Lifespan

Average Rated Life (hr)	100000
-------------------------	--------


Logistical data

Case Qty	1
Case Length (in)	99.803
Case Width (in)	5.709
Case Depth (in)	4.764
Case Cube (ft)	1.571
Case Weight (lbs)	14.511
Pallet Qty	70

Certificates & Standards

Certification Listing	RoHS / FCC / cULus
Replaceable light source (EPREL)	Not replaceable

Optional accessories

Product image	Product name	UPC
	VAPOR 3A LENS 4'	OS62616
	VAPOR 3A CLIPS	OS62618
	VAPOR 3A MOUNTING KIT	OS62619
	VAPOR 3A CLIPS 8'	OS66345
	Standalone Commissioning Remote REMOTE CONTROL	OS60105

EQUIPMENT / ACCESSORIES

– Stainless Steel mounting brackets and V-hooks

DOWNLOAD DATA

Spec Sheets and Product Documents		Document name
	Installation Guide	UltraLED Vapor Tight 3A Installation Guide
	Product Family Spec Sheet	UltraLED™ Dual Selectable Vapor Tight 3A

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.