

PRODUCT DATASHEET

WALL PACK CO 6A 120W 120-277V D 8 3CCT T2 BZ P

WALL PACK CUTOFF LINK™ | Cutoff Wall Pack with selectable CCT and wattage, compatible with optional LEDVANCE LINK™ sensor options



SUPERIOR
CLASS

Areas of application

- Building exteriors
- Outdoor corridors
- Walkways
- Stairwells

Product features

- Selectable CCT: 3000 K, 4000 K and 5000 K
- LEDVANCE LINK™ compatibility allows for customizable light via Bluetooth® Mesh
- Up to 140 LPW
- Traditional sizes allow seamless replacement of existing luminaires
- CRI > 80
- Selectable wattage and lumen output
- Type 2 and 4 distributions
- Energy savings up to 78 %

TECHNICAL DATA

Additional product data

Ordering Abbreviation	WALPAKC6A/S120UNVD8SC2/T2/BZ/P
Abbrev. With Packaging Info.	WALPAKC6AS120UNVD8SC2T2BZP 1/CS 1/SKU
NAED	62724
Family Brand Name	SUPERIOR CLASS
General Description	WALPAKC6A, WATTAGE SELECTABLE 75/95/120, 120-277V, 0-10V DIM, 80 CRI, CCT SELECTABLE 3000/4000/5000, TYPE II DISTRIBUTION, BRONZE, PHOTOCELL
Warranty	5 years

Electrical data

Nominal Wattage	75.00/95.00/120.00 W
Nominal voltage	120.00...277.00 V
Power factor	≥0.90
Total Harmonic Distortion	< 20 %

Photometrical data

Lumens	11000/14000/17000 lm
Efficacy	135 lm/W
Color Temperature/CCT	3000/4000/5000 K
Color Rendering Index (CRI)	80
Luminaire Type	Wall pack

Dimensions & Weight

Length	14.37 in
Width	9.33 in
Height	7.36 in
Product weight	9.04 lb

Materials & Colors

Luminaire Finish	Bronze
Housing color	Bronze
Housing	Aluminum
Mercury content	0.0 mg

Application & Mounting

Ambient temperature range	-40...+50 °C
Maximum Operating Temperature	122 °F
Minimum Operating Temperature	-40 °F

Dimming	Yes
Type of Dimming	0-10V
Mounting	Surface
Indoor/Outdoor	Outdoor
Replaceable light source	No
Primary Lamp Type	SMD

Lifespan

Average Rated Life (hr)	88000
-------------------------	-------

Logistical data

Case Qty	1
Case Length (in)	17.126
Case Width (in)	10.039
Case Depth (in)	11.614
Case Cube (ft)	1.156
Case Weight (lbs)	10.439
Pallet Qty	40

Certificates & Standards

Certification Listing	RoHS / FCC / cULus
Replaceable light source (EPREL)	Not replaceable

DOWNLOAD DATA

Spec Sheets and Product Documents		Document name
	Installation Guide	SUPERIOR CLASS WALPAKC6A INSTALL
	Product Family Spec Sheet	DUAL SELECTABLE CUTOFF WALL PACK
Photometric and lighting design files		Document name
	IES file (IES)	WALL PACK CUT-OFF 6A IES FILES

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.