

PRODUCT DATASHEET

WALL PACK OPTI-SELECT 100W 120-347V D 8 3CCTWARM ADJ BL P

WALL PACK CUTOFF OPTI-SELECT | Cutoff Wall Pack with selectable CCT, wattage and beam angle



Areas of application

- Walkways
- Building facades
- Perimeters
- Commercial buildings
- Schools

Product features

- OPTI-SELECT: Adjustable types 2, 3, and 4 distribution, no lens swap needed
- Up to 150 LPW
- CRI > 80
- Selectable wattage and lumen output
- DLC Premium: assures high energy efficient & eligible for utility rebates
- CONTROLS READY: sensor receptacle for standalone and LEDVANCE LINK, no wiring
- Integrated photocell that can be disabled in the field
- UV stabilized polycarbonate lenses, vandal resistant
- CCT Options vary per model: Selectable 3000/4000/5000K, Selectable Warm Spectrum 1800/2200/2700K or de-amber
- DarkSky Approved versions: sustainable luminaires designed to minimize light pollution and minimize environmental impact

TECHNICAL DATA

Additional product data

Ordering Abbreviation	WALPAKCP5100UNHD8SC15ADJBLP
Abbrev. With Packaging Info.	WALPAKCP5100UNHD8SC15ADJBLP 1/CS 1/SKU
NAED	67135
Family Brand Name	PERFORMANCE CLASS™
General Description	WALL PACK CUT OFF OPTISELECT PERFORMANCE CLASS, SELECTABLE WATTAGE 60/80/100W, SELECTABLE CCT 1800/2200/2700K, BLACK, PHOTOCELL, 120-347V
Warranty	5 years

Electrical data

Nominal Wattage	60.00/80.00/100.00 W
Nominal voltage	120.00...347.00 V
Power factor	≥0.90
Total Harmonic Distortion	< 20 %

Photometrical data

Lumens	6900/9200/11500 lm
Efficacy	115 lm/W
Color Temperature/CCT	1800/2200/2700 K
Luminaire Type	Wall pack

Dimensions & Weight

Length	13.35 in
Width	5.87 in
Height	8.27 in
Product weight	6.17 lb

Materials & Colors

Luminaire Finish	Black
Housing color	Black
Housing	Aluminum
Mercury content	0.0 mg

Application & Mounting

Ambient temperature range	-40...+50 °C
Maximum Operating Temperature	122 °F
Minimum Operating Temperature	-40 °F
Dimming	Yes

Type of Dimming	0-10V
Mounting	Surface
Indoor/Outdoor	Outdoor
Replaceable light source	No
Primary Lamp Type	SMD

Lifespan

Average Rated Life (hr)	100000
-------------------------	--------

Logistical data

Case Qty	1
Case Length (in)	15.866
Case Width (in)	10.669
Case Depth (in)	8.465
Case Cube (ft)	0.829
Case Weight (lbs)	7.207
Pallet Qty	50

Certificates & Standards

Certification Listing	RoHS / CSA / FCC / cULus
Replaceable light source (EPREL)	Not replaceable

Optional accessories

Product image	Product name	UPC
	WALL PACK OPTI-SELECT VISOR BLACK	OS67371

DOWNLOAD DATA

Spec Sheets and Product Documents		Document name
	Installation Guide	Install Manual Wall Pack Cutoff OPTI-SELECT Warm Spectrum
	Product Family Spec Sheet	LEDVANCE Luminaires WALL PACK CUTOFF OPTI-SELECT
Photometric and lighting design files		Document name
	IES file (IES)	WALL PACK WARM SPECTRUM IES LM79 SPD X

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.