

PRODUCT DATASHEET

WALL PACK 7A 40W 120-277V D 8 3CCT BZ P E

WALL PACK PERFORMANCE | Non Cutoff Wall Pack with selectable CCT and wattage



Areas of application

- Building exteriors
- Outdoor corridors
- Walkways
- Stairwells

Product features

- Selectable CCT: 3000 K, 4000 K and 5000 K
- Selectable wattage and lumen output
- UV stabilized polycarbonate lenses, vandal resistant
- Up to 151 LPW
- Integrated photocell that can be disabled in the field
- CRI > 80
- Energy savings up to 78 %
- DLC Premium: assures high energy efficient & eligible for utility rebates
- TAA Compliant

TECHNICAL DATA

Additional product data

Ordering Abbreviation	WALPAKN7A/S040UNVD8SC2/BZ/PE
Abbrev. With Packaging Info.	WALPAKN7AS040UNVD8SC2BZPE 1/CS 1/SKU
SKU UPC	0046135632280
NAED	63228
Family Brand Name	PERFORMANCE CLASS™
General Description	WALPAK7A, WATTAGE SELECTABLE 15/25/40, 120-277V, 0-10V DIM, 80 CRI, CCT SELECTABLE 3000/4000/5000, BRONZE, PHOTOCELL, EMERGENCY
Warranty	5 years

Electrical data

Nominal Wattage	40.00/25.00/15.00 W
Nominal voltage	120.00...277.00 V
Power factor	≥0.90
Total Harmonic Distortion	< 20 %

Photometrical data

Lumens	6000/3750/2250 lm
Efficacy	150 lm/W
Color Temperature/CCT	3000/4000/5000 K
Color Rendering Index (CRI)	80
Luminaire Type	Wall pack

Dimensions & Weight

Length	9.3 in
Width	14.5 in
Height	6.65 in
Product weight	14 lb

Materials & Colors

Luminaire Finish	Bronze
Housing color	Bronze
Housing	Aluminum
Mercury content	0.0 mg

Application & Mounting

Ambient temperature range	-40...+40 °C
Maximum Operating Temperature	104 °F

Minimum Operating Temperature	-40 °F
Dimming	Yes
Type of Dimming	0-10V
Mounting	Surface
Indoor/Outdoor	Outdoor
Replaceable light source	No

Lifespan

Average Rated Life (hr)	150000
-------------------------	--------

Logistical data

SKU Qty	1
Case Qty	1
Case Length (in)	15.158
Case Width (in)	11.024
Case Depth (in)	8.661
Case Cube (ft)	0.838
Case Weight (lbs)	14.617
SKU UPC	0046135632280
Pallet Qty	50

Certificates & Standards

Certification Listing	RoHS / FCC / cULus
Replaceable light source (EPREL)	Not replaceable

DOWNLOAD DATA

Spec Sheets and Product Documents		Document name
	Installation Guide	PERFORMANCE CLASS DUAL SELECTABLE WALPAKN7A INSTALL GUIDE
	Product Family Spec Sheet	NON-CUTOFF WALL PACK PERFORMANCE TAA

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.