

PRODUCT DATASHEET

WALL PACK 60W 277-480V D 8 3CCT BZ P

WALL PACK DUAL SELECTABLE | Non Cutoff Wall Pack with selectable CCT and wattage



Areas of application

- Building exteriors
- Outdoor corridors
- Walkways
- Stairwells

Product features

- Up to 150 LPW
- Selectable CCT: 3000 K, 4000 K and 5000 K
- Selectable wattage and lumen output
- DLC Premium: assures high energy efficient & eligible for utility rebates
- Ready for field installable standalone sensors, no wiring required
- Integrated photocell that can be disabled in the field
- Glass Lens

TECHNICAL DATA

Additional product data

Ordering Abbreviation	WALPAKN9AS060HUVD8SC2BZP
Abbrev. With Packaging Info.	WALPAKN9AS060HUVD8SC2BZP 1/CS 1/SKU
NAED	65864
Family Brand Name	PERFORMANCE CLASS™
General Description	PERFORMANCE WALL PACK 9A, SELECTABLE WATTAGE 35/45/60W, 277-480V, 0-10V DIM, 80 CRI, CCT SELECTABLE 3000/4000/5000K, BRONZE, PHOTOCELL
Warranty	5 years

Electrical data

Nominal Wattage	35.00/45.00/60.00 W
Nominal voltage	277.00...480.00 V
Power factor	≥0.90
Total Harmonic Distortion	< 20 %

Photometrical data

Lumens	5250/6750/9000 lm
Efficacy	140 lm/W
Color Temperature/CCT	3000/4000/5000 K
Color Rendering Index (CRI)	80
Luminaire Type	Wall pack

Dimensions & Weight

Length	14.37 in
Width	9.33 in
Height	6.3 in
Product weight	8.07 lb

Materials & Colors

Luminaire Finish	Bronze
Housing color	Bronze
Housing	Aluminum
Mercury content	0.0 mg

Application & Mounting

Ambient temperature range	-40...+50 °C
Maximum Operating Temperature	122 °F
Minimum Operating Temperature	-40 °F

Dimming	Yes
Type of Dimming	0-10V
Mounting	Surface
Indoor/Outdoor	Outdoor
Replaceable light source	No
Primary Lamp Type	SMD

Lifespan

Average Rated Life (hr)	100000
-------------------------	--------

Logistical data

Case Qty	1
Case Length (in)	17.638
Case Width (in)	10.984
Case Depth (in)	8.858
Case Cube (ft)	0.993
Case Weight (lbs)	9.081
Pallet Qty	40

Certificates & Standards

Certification Listing	RoHS / FCC / cULus
Replaceable light source (EPREL)	Not replaceable

Optional accessories

Product image	Product name	UPC
	Standalone Commissioning Remote HIBAY/AREA/CANOPY	OS65623
	Standalone PIR Motion sensor PIR3-Pin Screw-in 39ft IP65 12V	OS62664
	SENSOR PIR BZ	OS63748
	Standalone Microwave Motion Sensor 3-Pin Screw-in 49ft IP65 12V BR	OS65732

Product image	Product name	UPC
	ADAPTER WALPAKN9A SENSOR ADAPTER	OS63958
	WALPACK VISOR 9A SM BZ	OS63922
	WALPACK VISOR 9A MED BZ	OS63923
	WALPACK VISOR 9A LRG BZ	OS63924
	WALPACK WIRE GUARD 9A SMALL	OS63925
	WALPACK WIRE GUARD 9A MED	OS63926
	WALPACK WIRE GUARD 9A LRG	OS63927
	Standalone Microwave Motion Sensor 3-Pin Screw-in 49ft IP65 12V WH	OS65622

DOWNLOAD DATA

Spec Sheets and Product Documents		Document name
	Installation Guide	PERFORMANCE CLASS WALL PACK 9A
	Product Family Spec Sheet	LEDLUM193 DUAL SELECTABLE WALL PACK 9A
Photometric and lighting design files		Document name
	IES file (IES)	IES Files Wall Pack Non Cut Off 9A

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.