

# PRODUCT DATASHEET

## WALL PACK 120W 120-347V D 8 3CCT BZ P

WALL PACK DUAL SELECTABLE | Non Cutoff Wall Pack with selectable CCT and wattage



PERFOR-  
MANCE  
CLASS

### Areas of application

- Building exteriors
- Outdoor corridors
- Walkways
- Stairwells

### Product features

- Up to 150 LPW
- Selectable CCT: 3000 K, 4000 K and 5000 K
- Selectable wattage and lumen output
- DLC Premium: assures high energy efficient & eligible for utility rebates
- Ready for field installable standalone sensors, no wiring required
- Integrated photocell that can be disabled in the field
- Glass Lens

## TECHNICAL DATA

### Additional product data

|                              |                                                                                                                                                 |
|------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------|
| Ordering Abbreviation        | WALPAKN9AS120UNHD8SC2BZP                                                                                                                        |
| Abbrev. With Packaging Info. | WALPAKN9AS120UNHD8SC2BZP 1/CS 1/SKU                                                                                                             |
| NAED                         | 63767                                                                                                                                           |
| Family Brand Name            | PERFORMANCE CLASS™                                                                                                                              |
| General Description          | PERFORMANCE WALL PACK 9A, SELECTABLE WATTAGE<br>85/100/120W, 120-347V, 0- 10V DIM, 80 CRI, CCT SELECTABLE<br>3000/4000/5000K, BRONZE, PHOTOCELL |
| Warranty                     | 5 years                                                                                                                                         |

### Electrical data

|                           |                       |
|---------------------------|-----------------------|
| Nominal Wattage           | 85.00/100.00/120.00 W |
| Nominal voltage           | 120.00...347.00 V     |
| Power factor              | ≥0.90                 |
| Total Harmonic Distortion | < 20 %                |

### Photometrical data

|                             |                      |
|-----------------------------|----------------------|
| Lumens                      | 12750/15000/18000 lm |
| Efficacy                    | 135 lm/W             |
| Color Temperature/CCT       | 3000/4000/5000 K     |
| Color Rendering Index (CRI) | 80                   |
| Luminaire Type              | Wall pack            |

### Dimensions & Weight

|                |         |
|----------------|---------|
| Length         | 17 in   |
| Width          | 9 in    |
| Height         | 9 in    |
| Product weight | 8.75 lb |

### Materials & Colors

|                  |          |
|------------------|----------|
| Luminaire Finish | Bronze   |
| Housing color    | Bronze   |
| Housing          | Aluminum |
| Mercury content  | 0.0 mg   |

### Application & Mounting

|                               |              |
|-------------------------------|--------------|
| Ambient temperature range     | -40...+50 °C |
| Maximum Operating Temperature | 122 °F       |
| Minimum Operating Temperature | -40 °F       |

|                          |         |
|--------------------------|---------|
| Dimming                  | Yes     |
| Type of Dimming          | 0-10V   |
| Mounting                 | Surface |
| Indoor/Outdoor           | Outdoor |
| Replaceable light source | No      |
| Primary Lamp Type        | SMD     |

### Lifespan

|                         |        |
|-------------------------|--------|
| Average Rated Life (hr) | 100000 |
|-------------------------|--------|

### Logistical data

|                   |        |
|-------------------|--------|
| Case Qty          | 1      |
| Case Length (in)  | 20.984 |
| Case Width (in)   | 11.772 |
| Case Depth (in)   | 8.858  |
| Case Cube (ft)    | 1.266  |
| Case Weight (lbs) | 9.918  |
| Pallet Qty        | 40     |

### Certificates & Standards

|                                  |                    |
|----------------------------------|--------------------|
| Certification Listing            | RoHS / FCC / cULus |
| Replaceable light source (EPREL) | Not replaceable    |

### Optional accessories

| Product image                                                                       | Product name                                                       | UPC     |
|-------------------------------------------------------------------------------------|--------------------------------------------------------------------|---------|
|  | Standalone Commissioning Remote HIBAY/AREA/CANOPY                  | OS65623 |
|   | Standalone PIR Motion sensor PIR3-Pin Screw-in 39ft IP65 12V       | OS62664 |
|   | SENSOR PIR BZ                                                      | OS63748 |
|   | Standalone Microwave Motion Sensor 3-Pin Screw-in 49ft IP65 12V BR | OS65732 |

| Product image                                                                       | Product name                                                       | UPC     |
|-------------------------------------------------------------------------------------|--------------------------------------------------------------------|---------|
|    | ADAPTER WALPAKN9A SENSOR ADAPTER                                   | OS63958 |
|     | WALPACK VISOR 9A SM BZ                                             | OS63922 |
|     | WALPACK VISOR 9A MED BZ                                            | OS63923 |
|     | WALPACK VISOR 9A LRG BZ                                            | OS63924 |
|     | WALPACK WIRE GUARD 9A SMALL                                        | OS63925 |
|   | WALPACK WIRE GUARD 9A MED                                          | OS63926 |
|   | WALPACK WIRE GUARD 9A LRG                                          | OS63927 |
|  | Standalone Microwave Motion Sensor 3-Pin Screw-in 49ft IP65 12V WH | OS65622 |

## DOWNLOAD DATA

| Spec Sheets and Product Documents                                                  |                           | Document name                          |
|------------------------------------------------------------------------------------|---------------------------|----------------------------------------|
|  | Installation Guide        | PERFORMANCE CLASS WALL PACK 9A         |
|  | Product Family Spec Sheet | LEDLUM193 DUAL SELECTABLE WALL PACK 9A |
| Photometric and lighting design files                                              |                           | Document name                          |
|  | IES file (IES)            | IES Files Wall Pack Non Cut Off 9A     |

**DISCLAIMER**

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.