



Pass and Seymour
Kitchen Countertop Outlet, 15A, Matte White
Part No. CP498TR15W



The Kitchen Countertop Outlet is a code-compliant, UL 498-certified solution for kitchen islands and peninsulas, featuring a compact design and quick connection for easy installation. Passing a strict half-gallon spill test, the outlet ensures reliability and performance, offering the utmost safety for homeowners. The outlet can withstand strong wear and tear, with built-in corrosion/chemical resistance, and the surface-mount design makes everyday cleaning easy to help maintain long-term aesthetic. Purchase the outlet with an optional lid, which comes in four cast metal options to match or complement kitchen finishes.

Features & Benefits

Code Compliant with NEC 2023 406.5 (E), a standard to be adopted by roughly 50% of US states by the end of 2026	UL 498 rated for Countertop or Work Surface Assembly, ensuring reliability and performance.
Features a quick connecting termination tail that is wired above the counter and a hand-turn nut that requires no tools under the counter	Required installation downstream or connected to a GFCI breaker
Requires a 2-inch to 2.25-inch hole drilled into the countertop, which is dependent on the inclusion of a lid (an extra .25-inch is required with a lid)	Pair with optional cast metal iron available in four finishes: Matte Black, Matte White, Stainless Steel & Champagne Bronze
Compact, surface-mount design blends in with design aesthetic and kitchen finishes	Can withstand heavy wear and tear and is corrosion/chemical resistant
For use on kitchen island or peninsula countertops	Features tamper resistant shutters to protect against insertion of foreign objects
Smallest profile in the industry. Compared to the competition, it has a smaller diameter and less depth, taking up nearly 40% less space on and under the counter	Receptacle and tail assembly is suitable for install without a junction box
Patents pending	

Specifications

General Info

Product Line	Pass & Seymour	Color	Matte White
UPC Number	785007461251	Country Of Origin	China

Number of Receptacles		1	Features	Corrosion Resistant, Quick Connect Compatible, Spill-Resistant
Outlet Type		Tamper-Resistant	Application Sector	Hospitality, Multi-Dwelling Unit, Residential
Standard		UL 498, cULus Listed Receptacle, Countertop or Work Surface Assembly	Warranty Type	1-Year Limited Warranty
Dimensions				
Product Width US		2.3 in	Product Weight US	0.35 lb
Product Depth US		3.6 in	Product Height US	3.7 in
Listing Agencies / 3rd Party Agencies				
cULus Listed		Yes		
Technical Information				
Temperature Rise		Maximum 30°C temperature rise at full-rated current after 50 cycles of overload at 150% of rated current with direct current	Is Tamper-Resistant	Yes
Connection Location		Back Only	Amperage	15 A
Number of Poles		Double Pole	Wire Size	#14 - #10 AWG
Indoor/Outdoor		Indoor	NEMA Configuration Code	5-15R
Number of Phases		1	Wire Connection Type	Screw Terminals
Voltage		125.0 V		