

DFR40-S1W

Smooth Slim Downlight with Selectable Lumen Output and CCT,
4-inch Round Aperture



Leviton's 4-inch Smooth Slim Downlight with its ½-inch profile is designed for maximum flexibility. Field selectable lumen output and color temperature (CCT) gives you more options with the flick of a switch. IC rated and Wet Location rated for both indoor and outdoor covered ceiling applications. Smooth beam distribution and superior color quality ensure uniform, even illumination. Pair the DFR series with Leviton compatible dimmers for the desired light level needed for any space.

UPC Code : 078477037331

Country Of Origin : Please Contact
Customer Service

Compatible with the following Leviton Dimmers:

- SureSlide: 6672, 6674N, 66741, 66DF
- IllumaTech: IPL06, IPE04
- Decora Slide with Lever Edge: ESL01
- Decora Slide: DSL01, DSE06, DSM10
- Decora Digital: DDM06, DDE06, DDL06-1, DDL06-B
- Decora Smart Wi-Fi: D36HD, D26HD, D2ELV, D2MSD
- Decora Smart Z-Wave: ZW6HD
- Decora Evolve: VM2D3, VMDD3
- Toggle Slide: TSL01, TSM10
- Trimatron Rotary: RDL06, RNL06

Technical Information

Product Features

Product Aperture Size : 4-Inch Round

Input Power : 8/10W

Lumen Output : 650/820Lm

Input Voltage : 120VAC, 60Hz

Dimming Technology : 120V

Forward- or Reverse-Phase
Dimming down to 10%

Correlated Color

Temperature : Selectable

CCT: 2700K / 3000K / 3500K /
4000K / 5000K

Color Rendering Index : 90+

R9 : High color performance
with R9 value greater than 50

LED Life (Hours) : 50,000

hours @ 70% lumen
maintenance

Environmental Specifications

Operating Temperature : -20°
C (-4°F) to 40°C (104°F)

Listing : Suitable for Wet
Locations, Covered Ceilings

Material Specifications

Material : Die cast aluminum

Lens : Frosted Polycarbonate

Standards and Certifications

cETLus : Listed in accordance
with UL 1598 and CSA C22.2
No. 250.0

Finish : Matte White

Energy Rating : ENERGY
STAR® Certified

Listing : Compliant with ASTM
E283 (Air Leakage Rate 2.0
CFM or less)

Housing : Insulated Ceiling
(IC) Rated

Title 24 Compliant : Complies
with Title 24 Part 6 JA8 High
Efficacy LED Light Source
Requirements

National Electric Code (NEC)
: Suitable for use in clothes
closets when installed in
accordance with NFPA® 70
Section NEC® 410.16 (A)(1) (C)
(3) spacing requirements

Warranty

Warranty : Five (5) year
replacement after date of
purchase

Features and Benefits

- 1/2-Inch profile for low fixture depth
- Field selectable lumen output: 4-inch round delivers 650 lumens at 8 watts and 820 lumens at 10 watts
- Field selectable color temperature (2700K to 5000K)
- Smooth beam distribution for even illumination
- Light engine consists of 90+ CRI LEDs with R9>50
- Closed cell gasket included for use in wet location environments, covered ceilings
- Optional matte black trim ring accessories
- 120V forward- or reverse-phase dimming down to 10%
- ENERGY STAR® Certified
- IC-rated Die Cast Aluminum Housing
- 50,000 hours @ 70% lumen maintenance
- Five (5) year replacement after date of purchase

SPECIFICATION SUBMITTAL

JOB NAME: 	CATALOG NUMBERS: 	
JOB NUMBER: 		

Leviton Manufacturing Co., Inc

201 North Service Road, Melville, NY 11747

Telephone: +1-800-323-8920 · FAX: +1-800-832-9538 · Tech Line (8:30AM-7:30PM E.S.

T. Monday-Friday): +1-800-824-3005

Leviton Manufacturing of Canada, Ltd.

165 Hymus Boulevard, Pointe Claire, Quebec H9R 1E9 · Telephone: +1-800-461-2002 ·

FAX: +1-800-824-3005 ·

Leviton S. de R.L. de C.V.

Lago Tana 43, Mexico DF, Mexico CP 11290 · Tel.: (+52)55-5082-1040 · FAX: (+52) 5386- 1797 ·

Visit our Website at: www.leviton.com

© 2026 Leviton Manufacturing Co., Inc. All Rights Reserved. Subject to change without notice.

Leviton has a global presence.

If you would like to know where your local Leviton office is located please go to:

www.leviton.com/company/about-leviton/locations

© 2026 Leviton Manufacturing Co., Inc.