



8200-IGB

15 Amp Isolated Ground Duplex Receptacle/Outlet, Hospital Grade, Self-Grounding

Isolated Ground Duplex Receptacle Outlet, Heavy-Duty Hospital Grade, Smooth Face, 15 Amp, 125 Volt, Back or Side Wire, NEMA 5-15R, 2-Pole, 3-Wire, Self-Grounding - Brown

ROHS Compliant : Yes

Technical Information

AC Horsepower Ratings

Amperage : 15 A

At Rated Voltage : 1/2 HP

Current Limiting : Full Rated Current

Dielectric Voltage :
Withstands 3000V min

Grounding : Self-Grounding

Pole : 2

Temperature Rise : Max 30C
temperature rise at full rated current

Voltage : 125 VAC

Wire : 3

Electrical Specifications

Amperage : 15 A

Dielectric Voltage :
Withstands 3000V min

Flammability : Rated V-2 per UL 94

Grounding : Self-Grounding

Operating Temperature : -40°
C to 60°C

Pole : 2

Temperature Rise : Max 30C
temperature rise at full rated current

Voltage : 125 VAC

Wire : 3

Environmental Specifications

Body Material : PBT Polyester Blend

Clamp Nuts : 0.030" Brass

Color : Brown

Face Material : PBT Polyester Blend

Flammability : Rated V-2 per UL 94

Ground Clips : Brass

Ground Contacts : 0030"
Brass

Grounding Screw : #8 Hex
Head, Triple-Drive Bass

Line Contacts : 0.030"
Phosphor Bronze

Mounting Screws : Triple-
Drive Plated Steel

Material Specifications

At Rated Voltage : 1/2 HP

Body Material : PBT Polyester Blend

Clamp Nuts : 0.030" Brass

Color : Brown

Face Material : PBT Polyester Blend

Ground Clips : Brass

Ground Contacts : 0030"
Brass

Grounding Screw : #8 Hex
Head, Triple-Drive Bass

Line Contacts : 0.030"
Phosphor Bronze

Mounting Screws : Triple-
Drive Plated Steel

Shutter Mechanism : Acetal

Color :  Brown

UPC Code : 078477057285

Country Of Origin : Mexico

NEMA :  5-15R

Available Colors :



Gray

Ivory



Red

White

Operating Temperature : -40°
C to 60°C

Strap Material : Steel
(Galvanized G60)

Shutter Mechanism : Acetal

Terminal Clamp : Brass

Strap Material : Steel
(Galvanized G60)

Terminal Screws : #8 Triple-
Drive Brass

Terminal Screws : #8 Triple-
Drive Brass

Mechanical Specifications

Product Features

Product ID : Ratings are
permanently marked on device

Color : Brown

Screw Terminal Torque : 14-
18 in-lbs

Device Type : Duplex
Receptacle Outlet

Terminal Accom. : 14-10 AWG

Feature 4 : Smooth Face

Terminal ID : Brass-Hot,
Green-Ground, Silver-Neutral

Function : Isolated Ground

Termination : Back or Side
Wire

Grade : Heavy-Duty Hospital
Grade

Wire Type : Stranded or Solid

NEMA : 5-15R

Standards and Certifications

ANSI : C-73

Applicable Standards : UL
498, Fed Spec W-C-569, CSA
22.2 No. 42

CSA C22.2 No. 42 : File
152105

Certification/Listing : cULus,
NOM-ANCE

NEMA : WD-6

NOM : 057

RoHS : RoHS Compliant

UL Fed Spec WC-596 : File
E13399

UL498HG : File E13399

Warranty : 10-Year Limited

SPECIFICATION SUBMITTAL

JOB NAME: <input type="text"/>	CATALOG NUMBERS: <input type="text"/> <input type="text"/>	
JOB NUMBER: <input type="text"/>	<input type="text"/>	<input type="text"/>

Leviton Manufacturing Co., Inc

201 North Service Road, Melville, NY 11747

Telephone: +1-800-323-8920 · FAX: +1-800-832-9538 · Tech Line (8:30AM-7:30PM E.S.

T. Monday-Friday): +1-800-824-3005

Leviton Manufacturing of Canada, Ltd.

165 Hymus Boulevard, Pointe Claire, Quebec H9R 1E9 · Telephone: +1-800-461-2002 ·
FAX: +1-800-824-3005 ·

Leviton S. de R.L. de C.V.

Lago Tana 43, Mexico DF, Mexico CP 11290 · Tel.: (+52)55-5082-1040 · FAX: (+52)
5386- 1797 ·

Visit our Website at: www.leviton.com

© 2026 Leviton Manufacturing Co., Inc. All Rights Reserved. Subject to change without
notice.

Leviton has a global presence.

If you would like to know where your local Leviton office is located please go to:
www.leviton.com/company/about-leviton/locations

© 2026 Leviton Manufacturing Co., Inc.