



L5262-R

15 Amp Duplex Receptacle/Outlet, Industrial Grade, Self-Grounding

Duplex Receptacle Outlet, Heavy-Duty Industrial Specification Grade, Indented Face, 15 Amp, 125 Volt, Back or Side Wire, NEMA 5-15R, 2-Pole, 3-Wire, Self-Grounding - Red

Equipment ground contacts and terminal are constructed of a single piece of brass

Color :  Red

UPC Code : 078477897683

Country Of Origin : Mexico

Available Colors :



Technical Information

AC Horsepower Rating

Amperage : 15 A

Dielectric Voltage :
Withstands 3000 V minimum

Grounding : Self-Grounding

Horsepower Rating : 1/2 HP

Pole : 2

Temperature Rise : Max 30 °C
temperature rise at full rated
current

Voltage : 125 VAC

Wire : 3

Electrical Specifications

Amperage : 15 A

Dielectric Voltage :
Withstands 3000 V minimum

Flammability : Rated V-0 per
UL 94

Grounding : Self-Grounding

Operating Temperature : -40°
C to 75°C

Pole : 2

Temperature Rise : Max 30 °C
temperature rise at full rated
current

Voltage : 125 VAC

Wire : 3

Environmental Specifications

Body Material : PBT Polyester
Blend

Face Material : PBT Polyester
Blend

Flammability : Rated V-0 per
UL 94

Ground Clips : Brass

Ground Contacts : 0.030"
Brass

Grounding Screw : #8 Hex
Head, Triple-Drive Brass

Line Contacts : 0.030"
Phosphor Bronze

Mounting Screws : Triple-
Drive Plated Steel

Operating Temperature : -40°
C to 75°C

Material Specifications

Body Material : PBT Polyester
Blend

Face Material : PBT Polyester
Blend

Ground Clips : Brass

Ground Contacts : 0.030"
Brass

Grounding Screw : #8 Hex
Head, Triple-Drive Brass

Line Contacts : 0.030"
Phosphor Bronze

Mounting Screws : Triple-
Drive Plated Steel

Product ID : Ratings are
permanently marked on device

Shutter Mechanism : Acetal

Shutter Mechanism : Acetal

Strap Material : Steel
(Galvanized G60)

Terminal Clamps : Brass

Terminal Screws : #8 Triple-
Drive Brass

Strap Material : Steel
(Galvanized G60)

Terminal Accom. : #14 AWG -
#10 AWG

Terminal Clamps : Brass

Terminal ID : Brass - Hot,
Silver - Neutral, Green -
Ground,

Terminal Screws : #8 Triple-
Drive Brass

Termination : Back or Side
Wire

Wire Type : Stranded or Solid

Mechanical Specifications

Color : Red

Color / Feature : Red

Device Type : Duplex
Receptacle Outlet

Feature 4 : Indented Face

Grade : Heavy-Duty Industrial
Specification Grade

Product ID : Ratings are
permanently marked on device

Screw Terminal Torque : 14-
18 in-lbs

Terminal Accom. : #14 AWG -
#10 AWG

Terminal ID : Brass - Hot,
Silver - Neutral, Green -
Ground,

Termination : Back or Side
Wire

Wire Type : Stranded or Solid

Standards & Certifications

ANSI : C-73

Applicable Standards : UL
498, Fed Spec W-C-596, CSA
C22.2. No. 42

Certification/Listing : cULus,
NOM-ANCE

RoHS : RoHS Compliant

Product Features

ANSI : C-73

Applicable Standards : UL
498, Fed Spec W-C-596, CSA
C22.2. No. 42

Certification/Listing : cULus,
NOM-ANCE

Color : Red

Color / Feature : Red

Device Type : Duplex
Receptacle Outlet

Feature 4 : Indented Face

Grade : Heavy-Duty Industrial
Specification Grade

RoHS : RoHS Compliant

Warranty

Horsepower Rating : 1/2 HP

Warranty : 10-Year Limited

Patents *

MX321216
US8684771

MX324598
US8777674

This list is provided for patent marking purposes only. A good faith effort is made to maintain the accuracy and completeness of this list. No legal inference should be drawn from the omission of a patent from this list.

SPECIFICATION SUBMITTAL

JOB NAME: <input type="text"/>	CATALOG NUMBERS: <input type="text"/> <input type="text"/>	
JOB NUMBER: <input type="text"/>	<input type="text"/>	<input type="text"/>

Leviton Manufacturing Co., Inc

201 North Service Road, Melville, NY 11747

Telephone: +1-800-323-8920 · FAX: +1-800-832-9538 · Tech Line (8:30AM-7:30PM E.S.
T. Monday-Friday): +1-800-824-3005

Leviton Manufacturing of Canada, Ltd.

165 Hymus Boulevard, Pointe Claire, Quebec H9R 1E9 · Telephone: +1-800-461-2002 ·
FAX: +1-800-824-3005 ·

Leviton S. de R.L. de C.V.

Lago Tana 43, Mexico DF, Mexico CP 11290 · Tel.: (+52)55-5082-1040 · FAX: (+52)
5386- 1797 ·

Visit our Website at: www.leviton.com

© 2026 Leviton Manufacturing Co., Inc. All Rights Reserved. Subject to change without notice.

Leviton has a global presence.

If you would like to know where your local Leviton office is located please go to:
www.leviton.com/company/about-leviton/locations

© 2026 Leviton Manufacturing Co., Inc.