

L8500-100



Representative image shown

UPC Code : 078477213773

Country Of Origin : India

Pulling Grip, 0.25-0.36"

Pulling, Flexible Eye, Junior Pulling Grip, Galvanized Steel, 0.25" -0.36" Cable Diameter Range - Breakload is 450 LBS

ROHS Compliant : Yes

- Leviton wire mesh grips are built tough to provide the strength, reliability, and gripping force required for today's demanding wire mesh applications
- Pulling grips are reusable devices for pulling bare conductors, insulated wires, synthetic rope, wire rope, and fiber optic cable
- All pulling grip designs are fully tested to meet published break ratings without slipping

Technical Information

Material Specifications

Mesh Material : Galvanized

Mechanical Specifications

Approx. Break Strength : 450 lbs (204 kgs)

Bale Length : 2.5 in (63.5 mm)

Cable Range : 0.25 - 0.36 in (6.4 - 9.1 mm)

Duty : Light

Eye Type : Flex Eye

Mesh Length : 7.5 in (190.5 mm)

Mesh Style : Closed

Standards and Certifications : UL

Weave : Single Weave

Workload Safety Factor (lbs) : 150 lbs @ 3:1 (68 kgs @ 3:1)

Product Features

Device Type : Pulling Grip

Warranty

Warranty : 1-Year Limited

SPECIFICATION SUBMITTAL

<p>JOB NAME:</p> <input style="width: 100%; height: 20px;" type="text"/> <p>JOB NUMBER:</p> <input style="width: 100%; height: 20px;" type="text"/>	<p>CATALOG NUMBERS:</p> <table style="width: 100%; border-collapse: collapse;"> <tr> <td style="width: 50%; border: 1px solid black; height: 20px;"></td> <td style="width: 50%; border: 1px solid black; height: 20px;"></td> </tr> <tr> <td style="width: 50%; border: 1px solid black; height: 20px;"></td> <td style="width: 50%; border: 1px solid black; height: 20px;"></td> </tr> </table>				

Telephone: +1-800-323-8920 · FAX: +1-800-832-9538 · Tech Line (8:30AM-7:30PM E.S.
T. Monday-Friday): +1-800-824-3005

Leviton Manufacturing of Canada, Ltd.

165 Hymus Boulevard, Pointe Claire, Quebec H9R 1E9 · Telephone: +1-800-461-2002 ·
FAX: +1-800-824-3005 ·

Leviton S. de R.L. de C.V.

Lago Tana 43, Mexico DF, Mexico CP 11290 · Tel.: (+52)55-5082-1040 · FAX: (+52)
5386- 1797 ·

Visit our Website at: www.leviton.com

© 2026 Leviton Manufacturing Co., Inc. All Rights Reserved. Subject to change without
notice.

Leviton has a global presence.

If you would like to know where your local Leviton office is located please go to:
www.leviton.com/company/about-leviton/locations

© 2026 Leviton Manufacturing Co., Inc.