

# L8601-100

Pulling Grip, 0.50-0.62"

Pulling, Rotating Eye, Double Weave, Standard Length, Galvanized Steel, 0.5"-0.62" Cable Diameter Range - Breakload is 5600 LBS



Representative image shown

**UPC Code :** 078477579374

**Country Of Origin :** United Kingdom

**ROHS Compliant :** Yes

- Leviton wire mesh grips are built tough to provide the strength, reliability, and gripping force required for today's demanding wire mesh applications
- Pulling grips are reusable devices for pulling bare conductors, insulated wires, synthetic rope, wire rope, and fiber optic cable
- All pulling grip designs are fully tested to meet published break ratings without slipping

**Technical Information**

Mechanical Specifications

Product Features

**Approx. Break Strength :**  
5600LBS

**Device Type :** Pulling Grip

**Bale Length :** 7.1 in (180 mm)

**Cable Range :** 0.5"-0.62"

**Duty :** Medium

**Eye Type :** Rotating Barrel Eye

**Mesh Length :** 16.0"

**Mesh Style :** Closed

**Standards and Certifications :** UL

**Weave :** Double Weave

**Workload Safety Factor (lbs) :** 1,867 lbs @ 3:1 (847 kgs @ 3:1)

Material Specifications

Warranty

**Mesh Material :** Galvanized

**Warranty :** 1-Year Limited

**SPECIFICATION SUBMITTAL**

<p><b>JOB NAME:</b></p> <input style="width: 90%; height: 20px;" type="text"/>	<p><b>CATALOG NUMBERS:</b></p> <table border="1" style="width: 100%;"> <tr> <td style="width: 50%; height: 20px;"><input type="text"/></td> <td style="width: 50%; height: 20px;"><input type="text"/></td> </tr> <tr> <td style="width: 50%; height: 20px;"><input type="text"/></td> <td style="width: 50%; height: 20px;"><input type="text"/></td> </tr> </table>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>
<input type="text"/>	<input type="text"/>				
<input type="text"/>	<input type="text"/>				
<p><b>JOB NUMBER:</b></p> <input style="width: 90%; height: 20px;" type="text"/>					

Telephone: +1-800-323-8920 · FAX: +1-800-832-9538 · Tech Line (8:30AM-7:30PM E.S.  
T. Monday-Friday): +1-800-824-3005

**Leviton Manufacturing of Canada, Ltd.**

165 Hymus Boulevard, Pointe Claire, Quebec H9R 1E9 · Telephone: +1-800-461-2002 ·  
FAX: +1-800-824-3005 ·

**Leviton S. de R.L. de C.V.**

Lago Tana 43, Mexico DF, Mexico CP 11290 · Tel.: (+52)55-5082-1040 · FAX: (+52)  
5386- 1797 ·

**Visit our Website at: [www.leviton.com](http://www.leviton.com)**

© 2026 Leviton Manufacturing Co., Inc. All Rights Reserved. Subject to change without  
notice.

**Leviton has a global presence.**

If you would like to know where your local Leviton office is located please go to:

[www.leviton.com/company/about-leviton/locations](http://www.leviton.com/company/about-leviton/locations)

**© 2026 Leviton Manufacturing Co., Inc.**