

L9678-100

Support Grip, 2.00-2.50"

Support, Offset Eye, Rod Closing, Single Weave, Stainless Steel, 2.00"-2.50" Cable Diameter Range - Breakload is 3100 LBS, 9.0" Eye Length, 19.0" Mesh Length

ROHS Compliant : Yes

- Leviton wire mesh grips are built tough to provide the strength, reliability, and gripping force required for today's demanding wire mesh applications
- Support grips distribute the weight of the vertical or sloping runs of electrical and fiber optic cable, metal rods, tubing or hose over the entire length of the grip so the cable is not damaged
- Use of support grips avoids stress on cable connections and provides needed support for vertically hung cables



Representative image shown

UPC Code : 078477214220

Country Of Origin : China

Technical Information

Mechanical Specifications

Approx. Break Strength : 3,100LBS

Bale Length : 9 in (229 mm)

Cable Range : 2.00"-2.50"

Duty : Standard

Eye Type : Offset

Mesh Length : 19.0"

Mesh Style : Open - Rod Closing

Standards and Certifications : UL

Weave : Single Weave

Workload Safety Factor (lbs) : 310 lbs (140 kg)

Material Specifications

Mesh Material : 304 SS

Product Features

Device Type : Support Grip

Warranty

Warranty : 1-Year Limited

SPECIFICATION SUBMITTAL

<p>JOB NAME:</p> <input style="width: 90%; height: 20px;" type="text"/> <p>JOB NUMBER:</p> <input style="width: 90%; height: 20px;" type="text"/>	<p>CATALOG NUMBERS:</p> <table border="1" style="width: 100%; height: 40px;"> <tr> <td style="width: 50%; height: 20px;"></td> <td style="width: 50%; height: 20px;"></td> </tr> <tr> <td style="width: 50%; height: 20px;"></td> <td style="width: 50%; height: 20px;"></td> </tr> </table>				

Telephone: +1-800-323-8920 · FAX: +1-800-832-9538 · Tech Line (8:30AM-7:30PM E.S.
T. Monday-Friday): +1-800-824-3005

Leviton Manufacturing of Canada, Ltd.

165 Hymus Boulevard, Pointe Claire, Quebec H9R 1E9 · Telephone: +1-800-461-2002 ·
FAX: +1-800-824-3005 ·

Leviton S. de R.L. de C.V.

Lago Tana 43, Mexico DF, Mexico CP 11290 · Tel.: (+52)55-5082-1040 · FAX: (+52)
5386- 1797 ·

Visit our Website at: www.leviton.com

© 2026 Leviton Manufacturing Co., Inc. All Rights Reserved. Subject to change without
notice.

Leviton has a global presence.

If you would like to know where your local Leviton office is located please go to:

www.leviton.com/company/about-leviton/locations

© 2026 Leviton Manufacturing Co., Inc.