



M58AC-W

Tamper-Resistant USB Receptacle, Type A/C, 20 Amp 125 Volt, Commercial Grade, White - Lev-Lok

Lev-Lok Combination Tamper-Resistant Duplex Decora Receptacle and Dual-Port USB Type A-C Charger, NEMA 5-20R, 20A-125V, 2 Pole, 3-Wire Grounding Receptacle – White

Lev-Lok employs a simple twist and lock wiring module to provide a safe and secure connection. These devices are pre-wired for 3x faster installations and 5x faster swap outs than traditional wiring. The speed and ease of Lev-Lok allows for optimal time, labor, and cost savings.

Color :  White

UPC Code : 078477433898

Country Of Origin : China

NEMA :  5-20R

Available Colors :



The M58AC:

- One Type A and one Type C USB port with a combined total of 5.1A of charging power
- Type A USBs are the most recognized and commonly used USB port, used in most desktops, laptops, and tablets, while Type C USBs are emerging as the latest standard for charging and transferring data
- Common applications: health care facilities, lobbies & waiting rooms, airports, hospitality, and educational institutions
- **For use with MSTWL Lev-Lok wiring modules only, modules sold separately**

Technical Information

Electrical Specifications

Amperage : 20 A
Current Interrupting : Certified for full-rated current and voltage
Dielectric Voltage : 2000 VAC
Grounding : Self-Grounding
Horsepower Rating : 1 hp
Pole : 2
Temperature Rise : Max 30°C
Voltage : 125 VAC
Wire : 3

Environmental Specifications

Flammability : Rated V-0 per UL 94
Operating Temperature : Maximum Continuous 40°C, Minimum -10°C (w/o impact)

Material Specifications

Body Material : PBT
Face Material : Thermoplastic
Ground Clips : Brass
Ground Contacts : Brass

Mechanical Specifications

Product ID : Ratings are marked on device
Strap Construction : Through-Strap
Termination : Modular

Locking Pins : Solid Brass

Mounting Screws : #6 Plated Steel

Mounting Strap : Galvanized Steel

Shutter Material : Thermoplastic

Shutter Mechanism : Acetal

Product Features

Brand : Lev-Lok

Color : White

Device Type : Combination Device

Feature : USB Type A and USB Type C|Tamper-Resistant

Grade : Commercial Specification Grade

NEMA : 5-20R

Standards & Certifications

Applicable Standards : UL 498, CSA C22.2, No. 42, UL 1310, UL 94, NOM, FCC Class B

NEMA : WD-1 and WD-6

USB Specifications

Single Port Charging Power : 15W

Total Charging Power : 25W

USB Cable Compatible : Type A and Type C

USB Charger : 5.1A

Warranty

Warranty : 2-Year Limited

Patents*

US7355117	US9368982
US7357652	CA2857863
CA2655707	US7666010
CA2621644	US7820909
CA2624409	US9496726
US8242362	US7868719
US8096818	CA2677283
CA2667092	MX338817

This list is provided for patent marking purposes only. A good faith effort is made to maintain the accuracy and completeness of this list. No legal inference should be drawn from the omission of a patent from this list.

SPECIFICATION SUBMITTAL

JOB NAME: <input type="text"/>	CATALOG NUMBERS: <input type="text"/> <input type="text"/>	
JOB NUMBER: <input type="text"/>	<input type="text"/> <input type="text"/>	

Leviton Manufacturing Co., Inc

201 North Service Road, Melville, NY 11747

Telephone: +1-800-323-8920 · FAX: +1-800-832-9538 · Tech Line (8:30AM-7:30PM E.S.
T. Monday-Friday): +1-800-824-3005

Leviton Manufacturing of Canada, Ltd.

165 Hymus Boulevard, Pointe Claire, Quebec H9R 1E9 · Telephone: +1-800-461-2002 ·
FAX: +1-800-824-3005 ·

Leviton S. de R.L. de C.V.

Lago Tana 43, Mexico DF, Mexico CP 11290 · Tel.: (+52)55-5082-1040 · FAX: (+52)
5386- 1797 ·

Visit our Website at: www.leviton.com

© 2026 Leviton Manufacturing Co., Inc. All Rights Reserved. Subject to change without
notice.

Leviton has a global presence.

If you would like to know where your local Leviton office is located please go to:
www.leviton.com/company/about-leviton/locations

© 2026 Leviton Manufacturing Co., Inc.