



UPC Code : 078477472286

Country Of Origin : Mexico

MDS6-ST

60 A Stainless Steel Slope Top Disconnect Switch

60 Amp Non-Fused PowerSwitch Stainless Steel Slope Top Disconnect Switch, 600 Volt, Type 304 Non-Magnetic Stainless Steel Enclosure, 15 Degree Slope

Powerswitch® safety disconnect switches are designed for superior performance in food and beverage processing, manufacturing, marinas and shipyards, and OEM applications. Built to withstand the rigors of these harsh environments, these devices address the needs of safety, washdown, reduced downtime and code compliance, and are backed by a leading 3 year warranty.

- Features a 15° slope, pushing water and debris away from the door, handle, gasket and front of the device
- Watertight, dust-tight, submersible and suitable for high pressure, high temperature washdown
- Overmold handle provides firm grip, durability and withstands washdown

Technical Information

Electrical Specifications

Amperage : 60 A

Current Interrupting : Certified for full-rated current and voltage

Dielectric Voltage : 1000 V plus twice rated voltage for 1 minute

Endurance : 6,000 cycles inductive motor type load

Short Circuit Current Rating : 10KA

Voltage : 600 VAC

Environmental Specifications

Ingress Protection : NEMA/UL 50E Type 3R, 4X, 12, 13; IP66, IP67, IP68; IP69K (per ISO 20653)

Operating Temperature : -40° C to 75°C

UV Resistance : Exposed materials are UV stabilized

Material Specifications

Enclosure Material : 16 Gauge Type 304 Stainless Steel

Gasket : Polyurethane Formed-In-Place-Foam Gasket (FIPFG), UL 50E Approved

Handle Material : Base: PBT Overmold: TPE

Mechanical Specifications

Feature : Slope Top

Product ID : Part of internal and external label

Terminal Accom. : 14-8 AWG

Terminal ID : In accordance with UL and international conventions

Standards and Certifications

Warranty

CE : CE Marked - Low Voltage Directive (LVD) 2014/35/EU **Warranty** : 3-Year Limited

IEC : 60529

NEMA : 250

NOM : NOM-ANCE

cULus : Listed to UL 60947-4-1 (supersedes UL 508) and CSA-C22.2 no. 60947-4-1

Patents *

CA2939247

MX374848

This list is provided for patent marking purposes only. A good faith effort is made to maintain the accuracy and completeness of this list. No legal inference should be drawn from the omission of a patent from this list.

SPECIFICATION SUBMITTAL

JOB NAME: <input type="text"/>	CATALOG NUMBERS: <input type="text"/>	<input type="text"/>
JOB NUMBER: <input type="text"/>	<input type="text"/>	<input type="text"/>

Leviton Manufacturing Co., Inc

201 North Service Road, Melville, NY 11747

Telephone: +1-800-323-8920 · FAX: +1-800-832-9538 · Tech Line (8:30AM-7:30PM E.S.

T. Monday-Friday): +1-800-824-3005

Leviton Manufacturing of Canada, Ltd.

165 Hymus Boulevard, Pointe Claire, Quebec H9R 1E9 · Telephone: +1-800-461-2002 ·

FAX: +1-800-824-3005 ·

Leviton S. de R.L. de C.V.

Lago Tana 43, Mexico DF, Mexico CP 11290 · Tel.: (+52)55-5082-1040 · FAX: (+52)

5386- 1797 ·

Visit our Website at: www.leviton.com

© 2026 Leviton Manufacturing Co., Inc. All Rights Reserved. Subject to change without notice.

Leviton has a global presence.

If you would like to know where your local Leviton office is located please go to:

www.leviton.com/company/about-leviton/locations

© 2026 Leviton Manufacturing Co., Inc.