

MT163-IG

Lev-Lok Isolated Ground Tamper-Resistant Duplex Receptacle

Lev-Lok Decora Plus Isolated Ground Duplex Receptacle Outlet, Heavy-Duty Industrial Specification Grade, Tamper-Resistant, Smooth Face, 20 Amp, 125 Volt, Modular, NEMA 5-20R, 2-Pole, 3-Wire, Self-Grounding - Orange **Mating Lev-Lok Wiring Module Required for Use**



Color :  Orange

UPC Code : 078477501900

Country Of Origin : Mexico

NEMA :  5-20R

Available Colors :

- | | | |
|---|---|---|
|  |  |  |
| Brown | Blue | Black |
|  |  |  |
| Gray | Ivory | Black |
|  |  |  |
| Gray | Ivory | Red |
|  |  |  |
| Light Almond | White | Red |
|  |  | |
| Light Almond | White | |

**Calculate
Time &
Money
Saved with
the Lev-Lok
Savings
Calculator!**

Technical Information

AC Horsepower Ratings

Horsepower Rating : 1 HP

Electrical Specifications

Amperage : 20 A

Current Limiting : Full Rated Current

Dielectric Voltage :
Withstands 2000V per UL498

Grounding : Self-Grounding

Pole : 2

Temperature Rise : Max 30C
after 250 cycles OL at 200
percent rated current

Voltage : 125 VAC

Wire : 3

Environmental Specifications

Operating Temperature : -40°
C to 60°C

Material Specifications

Body Material : Nylon

Color : Orange

Face Material : Nylon

Ground Clips : Brass

Isolated Ground System :
Brass

Line Contacts : 0.040" Thick
Solid Brass

Locking Pins : Solid Brass

Shutter Mechanism : Delrin®
Acetal

Strap Material : Galvanized
Steel

Mechanical Specifications

Lead Identification : Leads
identified in accordance with UL
498 (black, white & green)

Product ID : Markings are
permanently marked on device

Termination : Modular

Product Features

Brand : Lev-Lok Decora Plus

Color : Orange

Device Type : Duplex
Receptacle Outlet

Feature : Tamper-
Resistant|Smooth Face

Function : Isolated Ground

Grade : Heavy-Duty Industrial
Specification Grade

NEMA : 5-20R

Standards and Certifications

ANSI : C-73

CSA C22.2 No. 42 : File
152105

NEMA : WD-6

NOM : 057

RoHS : Compliant

UL 498 : File E13399

UL Fed Spec WC-596 : File
E13399

Warranty : 10-Year Limited

SPECIFICATION SUBMITTAL

JOB NAME: <input type="text"/>	CATALOG NUMBERS: <input type="text"/>	
JOB NUMBER: <input type="text"/>	<input type="text"/>	<input type="text"/>

Leviton Manufacturing Co., Inc

201 North Service Road, Melville, NY 11747

Telephone: +1-800-323-8920 · FAX: +1-800-832-9538 · Tech Line (8:30AM-7:30PM E.S.
T. Monday-Friday): +1-800-824-3005

Leviton Manufacturing of Canada, Ltd.

165 Hymus Boulevard, Pointe Claire, Quebec H9R 1E9 · Telephone: +1-800-461-2002 ·
FAX: +1-800-824-3005 ·

Leviton S. de R.L. de C.V.

Lago Tana 43, Mexico DF, Mexico CP 11290 · Tel.: (+52)55-5082-1040 · FAX: (+52)
5386- 1797 ·

Visit our Website at: www.leviton.com

© 2026 Leviton Manufacturing Co., Inc. All Rights Reserved. Subject to change without notice.

Leviton has a global presence.

If you would like to know where your local Leviton office is located please go to:

www.leviton.com/company/about-leviton/locations

© 2026 Leviton Manufacturing Co., Inc.