






— LBI Versatility (common applications)

APPLICATION	DECORATIVE PENDENT MOUNT FIXTURES  Office Space		RECOMMENDED ACCESSORIES	 Suspended In-Line Bracket Kit  Linking Cables  Seamless Connectors
APPLICATION	CONTINUOUS RUN  Warehouse Space	 	RECOMMENDED ACCESSORIES	 Seamless Connectors  OC2 Sensor
APPLICATION	COVE LIGHTING  Hospitality	 	RECOMMENDED ACCESSORIES	 45 Degree Bracket  Seamless Connectors  Linking Cables
APPLICATION	COOLERS  Grocery or Convenient Stores	 	RECOMMENDED ACCESSORIES	 Seamless Connectors  Linking Cables
	INCOMING POWER KIT One kit is required per continuous run of LBI RP-LBI-G1-IP-3F-DIM	INCLUDED WITH KIT   Used to hard wire the incoming power cable into fixture or junction box.  — Incoming Power Cable / Pigtail — Service Disconnect & Abrasion Protection Grommet		


CONNECTORS & CONTROLS



LINKING CABLES

RP-LBI-LC-6IN-DIM
RP-LBI-LC-6IN-NODIM
RP-LBI-LC-12IN-DIM
RP-LBI-LC-12IN-NODIM
RP-LBI-LC-18IN-DIM
RP-LBI-LC-18IN-NODIM

Quickly link LBI together in fixtures, around corners and more.
AVAILABLE IN 6", 12" OR 18"



DIM



NO-DIM

SEAMLESS CONNECTORS

RP-LBI-SSC-DIM-10P
RP-LBI-SSC-NODIM-10P

Connect LBI together resulting in a seamless run of lighting.



OC2 SENSOR KIT

RP-LBI-OC2 (SINGLE PACK)

Tri-Level, remote programmable high frequency motion and daylight sensor designed to easily integrate with the LBI bars.



EMERGENCY DRIVER (EMG-H SERIES)

RP-LBI-EMG1-25W

Emergency solution for LBI. It allows the LBI to be used for normal and emergency operation.



4.7IN SPACER CONNECTOR

RP-LBI-SRC-4.7IN (SINGLE PACK)

Use the 4.7in spacer connector to bring the length of the bar system to a standard dimension.



CORD WITH PLUG & ON/OFF SWITCH

RP-LBI-G1-IP-2F-120V-SW
RP-LBI-G1-IP-7F-120V-SW

Used when powering the LBI bars from a standard '3 prong' electrical outlet (NEMA 5-15 receptacle).
AVAILABLE IN 2' OR 7'

NOTE electrical rating allows up to 10 LBI units connected with linking cables and/or seamless connectors when using the cord w/ plug.

MOUNTING ACCESSORIES



SURFACE MOUNT MAGNETIC CLIP

RP-LBI-SMM-10P (10 PACK ONLY)

The most universal method for attaching the LBI to a wall, ceiling, or fixture.


(2x magnetic clips, 4x screws, 1x FWFC cover included with every LBI)



SUSPENDED IN-LINE BRACKET KIT

RP-LBI-SIL-KIT-10P (10 PACK ONLY)

Fastens over the junction of 2 LBI to keep them straight in-line and provides mounting points for common suspension methods.



UP/DOWN CLIP

RP-LBI-UDC-10P (10 PACK ONLY)

Use the Up/Down clip with our suspended in-line kit to clip a shorter LBI to provide up-light.



BLADE CLIP

RP-LBI-BLC-10P (10 PACK ONLY)


Designed for fixtures that have thin sheet metal or plastic film reflectors commonly found on high bays.



45 DEGREE BRACKET/CLIP

RP-LBI-45DEG

Holds the LBI at 45 degrees to better distribute the light in the desired direction.



T-BAR CLIP

RP-LBI-T1516-10P (10 PACK ONLY)

The fastest way to mount a light bar to a T-Bar grid ceiling. Works with standard 15/16" grid only.