

| | | | |
|-------------|-----|------|----------|
| Version | 2.0 | Date | 12/23/25 |
| Prepared By | JC | | |

| PRODUCT SPECIFICATION | |
|-----------------------|-----------------|
| Category | Flush Mount |
| Item Number | 9766 |
| Stock Code | LED4FMC-65LCCT5 |
| Mounting | Ceiling Mount |
| Housing Color | White |



| ELECTRICAL CHARACTERISTICS | | | |
|----------------------------|-------|-------------------------|-------|
| Rated Wattage (W) | 9 | Replacement Wattage (W) | 75 |
| Tested Wattage (W) | - | | |
| Input Voltage (V) | 120V | Surge Protect Level | 2.5KV |
| Voltage Frequency (Hz) | 50/60 | Dimmable | Triac |
| Input Current (A) | 0.08 | AUX (12V) Line | - |
| Power Factor | >0.9 | | |
| THD | - | | |

| PHOTOMETRIC CHARACTERISTICS | | | |
|-----------------------------|--------|----------------|------------------------|
| Lumen (lm) | 650 | CCT (K) | CCT5 (27/30/35/40/50K) |
| Efficacy (lm/w) | 72lm/w | Beam Angle (°) | 110° |
| CRI | >90 | | |

| GENERAL CHARACTERISTICS | |
|----------------------------|--------------|
| Operating Temperature (°F) | -4°F ~ 104° |
| Storage Temperature (°F) | -40°F ~ 185° |
| IP Rating | Wet Location |
| IK Rating | - |
| Rated Life (Hrs) | 35,000 |
| Warranty (Yrs) | 3 |

| ACCESSORIES | | |
|-------------|------------|-------------|
| Item # | Stock Code | Description |
| | | |
| | | |
| | | |
| | | |
| | | |

| PRODUCT DIMENSIONS | | |
|----------------------|-------|------|
| Diameter- in / (mm) | 3.50" | 89 |
| Width- in / (mm) | 5.91" | 150 |
| Height- in / (mm) | 1.26" | 32.1 |
| EPA (ft²) | - | |
| Weight (lbs) | - | |
| Mounting Height (ft) | 8~10 | |
| Cable Length (ft) | - | |

| CERTIFICATIONS | | | |
|--------------------|----------|------|---|
| UL/ETL | ETL/cETL | CEC | |
| NSF/ETL Sanitation | | JA8 | ✓ |
| Energy Star | | FCC | ✓ |
| DLC | | RoHs | |

| DOCUMENTS | | | |
|-----------|--|-------------|---|
| LM79 | | IES File | ✓ |
| LM80 | | Dimmer List | |
| | | | |
| | | | |

| COMMENTS |
|----------|
| |