

Version	2.0	Date	12/23/25
---------	-----	------	----------

Prepared By	JC
-------------	----

PRODUCT SPECIFICATION	
Category	Emergency Exit Sign
Item Number	9825
Stock Code	LEDEX-EL/SM-GRN/RED-WH
Mounting	Surface Mount/Wall Mount
Housing Color	White



ELECTRICAL CHARACTERISTICS			
Rated Wattage (W)	1	Replacement Wattage (W)	2
Tested Wattage (W)	1		
Input Voltage (V)	120-277V	Surge Protect Level	-
Voltage Frequency (Hz)	50/60	Dimmable	-
Input Current (A)	0.035	AUX (12V) Line	No
Power Factor	-		
THD	-		

PHOTOMETRIC CHARACTERISTICS			
Lumen (lm)	-	Color	Red/Green
Efficacy (lm/w)	-	Beam Angle (°)	-
CRI	-		

GENERAL CHARACTERISTICS	
Operating Temperature (°F)	32°F ~ 104°
Storage Temperature (°F)	32°F ~ 104°
IP Rating	Dry
IK Rating	-
Rated Life (Hrs)	50,000
Warranty (Yrs)	2

ACCESSORIES		
Item #	Stock Code	Description
P10688	MT-TBAR-LEDEX-EL/SM	T Grid T-Bar Mounting Kit

PRODUCT DIMENSIONS		
Width-Overall in / (mm)	12.13" / 308	
Width- in / (mm)	11.24" / 285.5	
Depth- in / (mm)	1.82" / 46.3	
Height- Overall in / (mm)	9.79" / 248.6	
Weight (lbs)	2.4	
Mounting Height (ft)	-	
Cable Length (ft)	-	

CERTIFICATIONS			
UL/ETL	UL	CEC	
NSF/ETL Sanitation		JA8	
Energy Star		FCC	✓
DLC		RoHs	

DOCUMENTS			
LM79		IES File	
LM80		Dimmer List	
TAA Compliant			

COMMENTS