Project / Job Name:

Location:

Fixture Type:

Notes:



**65-1513** - LED Linear High Bay; 320/295/255 Wattage Selectable; 3K/4K/5K CCT Selectable; Beam Angle Selectable; White Finish; 120-347 Volt

## GENERAL

| | |
|---|---|
| Company | NUVO |
| EA Height | 3.15 |
| EA Width | 13.19 |
| EA Length | 22.83 |
| Bulb Included | Integrated |
| Chain Length (in) | 41 |
| Material | Die-cast Aluminum |
| Fixture Type | Linear Hi-Bay |
| Product Notes | Default Wattage: 320W |
| Status | Active |
| Style | Utility |
| Surge Protection | Built-in surge protection - 6KV |
| Total Harmonic Distortion | <20% |
| CCT Selectable | Yes |
| Wattage Selectable | Yes |
| Finish Family | White |
| Amps | 2.670-0.920/2.460-0.850/2.130-0.730A |
| Integrated Features | Integrated Sensor Port |
| Lens Finish | Clear |
| Lens Material | Polycarbonate (PC) |
| Lensed | Yes |
| Starfish Operational Humidity | 20% to 90% R.H. |
| Power Factor | >0.9 |
| Indoor Outdoor | Indoor |
| Product Technology | LED |
| Fluor Equiv | 475W-550W |
| Serviceable Battery | No |
| Battery Indicator | No |
| Digital Display | No |

## ELECTRICAL

| | |
|---|---|
| CCT (Kelvin Temp) | 3000K/4000K/5000K |
| Dimmable | Yes-Dimmable |
| Hours Rated | 50000 |
| Beam Angle (degree) | 45x100/65x95/90x90 |
| Color Temp | Soft White to Natural Light |
| CRI | 80+ |
| Dimming Type | 0-10V Dimming |
| Operating Frequency | 50/60Hz |
| Operating Temp | -40F to +122F (-40C to +50C) |
| HID Equivalent | 475W-550W |
| Lumens | 37800L-48500L |
| Volts | 120V-347V |
| Watts | 320W/295W/255W |
| Max Lumens | 48500L |

## PHYSICAL

| | |
|---|---|
| Lamp Base | Integrated |
| Finish | WHITE |
| ANSI Base | Integrated |
| Lamp Type | Integrated LED |
| Fixture Shape | Linear |
| Mounting Procedure | Ceiling |

## ADDITIONAL INFO

| | |
|---|---|
| Warranty | 5-Years |

## PACKAGING

| | |
|---|---|
| UPC | 045923412493 |
| Case Cube | 0.5489 |
| Case Height | 3.15 |
| Case Length | 22.83 |
| Case Quantity | 1 |
| Case UPC | 10045923412490 |
| Case Weight | 10.89 |
| Case Width | 13.19 |
| EA Cube | 0.5489 |
| EA Height | 3.15 |
| EA Length | 22.83 |
| EA Quantity | 1 |
| EA Weight | 10.89 |
| EA Width | 13.19 |
| Pack Type | Box |
| Web Height | 1.89 |
| Web Length | 22.0 |
| Web Width | 12.4 |

## COMPLIANCE

| | |
|---|---|
| CA Prop 65 | Lead |
| DLC ID | S-9CCRBJ |
| FCC Compliant | Yes |
| IP Rating | IP20 |
| Location Rating | Damp |
| NSF Approved | No |
| ROHS Compliant | Yes |
| Safety Listing | cULus - Listed |
| California Ban | Lawful for sale |
| DLC Approved | Yes |
| Title 20 | Exempt |
| T24/JA8 Compliant | No |



© Satco Products, Inc.
All rights reserved 2026