



Project / Job Name:

Location:

Fixture Type:

Notes:

65-1541 - LED Flood Light; 80/60/45 Wattage Selectable; 3K/4K/5K CCT Selectable; Beam Angle Selectable; Bronze Finish; 120-347 Volt



GENERAL

Company	NUVO
EA Height	12.6
EA Width	4.92
EA Length	12.32
Bulb Included	Integrated
Material	Die-cast Aluminum
Fixture Type	Flood Light
Product Notes	Default Wattage: 80W
Status	Active
Style	Utility
Surge Protection	Built-in surge protection - 6KV
Total Harmonic Distortion	<20%
Wire Color	Black
CCT Selectable	Yes
Wattage Selectable	Yes
Finish Family	Bronze
Amps	0.670-0.230/0.500-0.170/0.380-0.130A
Integrated Features	Integrated Photocell
Lens Finish	Clear
Lens Material	Glass
Lensed	Yes
Starfish Operational Humidity	20% to 90% R.H.
Photo Cell	Has Photocell
Power Factor	>0.9
Indoor Outdoor	Outdoor
Product Technology	LED
Incandescent Equivalent	200W-300W

ELECTRICAL

CCT (Kelvin Temp)	3000K/4000K/5000K
Dimmable	Yes-Dimmable
Hours Rated	50000
Beam Angle (degree)	135x125/120x120/90x90
Color Temp	Soft White to Natural Light
CRI	80+
Dimming Type	0-10V Dimming
Operating Frequency	50/60Hz
Operating Temp	-40F to +122F (-40C to +50C)
HID Equivalent	220W-300W
Lumens	6757L-11846L
Volts	120V-347V
Watts	80W/60W/45W

PHYSICAL

Lamp Base	Integrated
Finish	BRONZE
ANSI Base	Integrated
Lamp Type	Integrated LED
Fixture Shape	Rectangle

ADDITIONAL INFO

Warranty	5-Years
----------	---------

PACKAGING

UPC	045923412592
Case Cube	3.0256
Case Height	13.39
Case Length	25.24
Case Quantity	6
Case UPC	10045923412599
Case Weight	38.28
Case Width	15.47
EA Cube	0.442
EA Height	12.6
EA Length	12.32
EA Quantity	1
EA Weight	5.46
EA Width	4.92
Pack Type	Box
Web Height	9.74
Web Length	9.76
Web Width	3.62

COMPLIANCE

Bug Rating	B4-U0-G5
CA Prop 65	Lead
DLC ID	S-00T2FY
FCC Compliant	Yes
IP Rating	IP65
Location Rating	Wet
NSF Approved	No
ROHS Compliant	Yes
Safety Listing	cULus - Listed
California Ban	Lawful for sale
DLC Approved	Yes
Title 20	Exempt
T24/JA8 Compliant	No