



S29914

14T8/LED/48-835/BP 120-277V
 14 watt T8 LED; Medium bi-pin base; 3500K; 50000 Average rated hours; 1700 lumens

Features

- All glass tube
- Approved for use with tube guards
- Direct wire 120-277V line voltage*
- NSF Approved
- No ballast or external driver required
- Built-in shock resistant circuit - (not hot until both ends are installed)



S29914

*Existing wiring to both sockets can remain in place

*Will work on both shunted or non-shunted sockets

Item Number	UPC	Voltage	Watts	Operating Frequency	Fluorescent Equivalent	Lamp Shape	Base	
S29914	045923299148	120-277	14	50/60Hz	25W-32W	T8	Medium Bi-Pin	
ANSI Base	Lamp Code	Dimmable/Non-Dimmable		Finish	MOL In Inches	MOD In Inches	Initial Lumens	Average Rated Hours
G13	14T8/LED/48-835/BP 120-277V	Non-Dimmable		White	48"	1.00"	1700	50000
Kelvin Temp	Color	CRI	Beam Spread Deg	Pack	Package Type	CEC Status	DLC ID:	
3500	Neutral White	82	210	25	Box	Lawful for sale in California	PL3F5T69IOD6 DLC Search	
RoHS Compliant		UL or ETL Listed		UL Classification			Warranty	
Yes		Yes		cULus Classified - Damp Location Rated			5 Year Limited	



National Toll-Free:
800.43.SATCO
(800.437.2826)
www.satco.com

Distribution Centers:
New York, Florida, Texas,
Washington, California,
Puerto Rico

Corporate Offices:
110 Heartland Blvd.,
Brentwood, NY 11717
800.437.2826 631.243.2022
Fax 631.243.2027

