



S9734

14T8/LED/48-830/DR

14 watt T8 LED; Medium bi-pin base; 3000K; 50000 average rated hours; 1800 lumens

Features

- Direct Replacement - for use on Instant Start and Rapid Start ballasts with no rewiring required*
- Solid State LED lighting
- High efficacy
- Long life
- 5 year Limited warranty
- Dimmable*
- Compatible with emergency ballasts*
- All glass tube

*May not be compatible with all rapid start, dimmable, and emergency ballasts.

View:

[Ballast Compatibility Chart](#)

[Dimming Ballast Compatibility Chart](#)

[Emergency Ballast Compatibility Chart](#)

Approved for enclosed fixtures when used only on low or normal ballast factor systems

This item has been discontinued.

Possible replacement:

- [S9934](#)



S9734

Item Number	UPC	Voltage	Watts	Fluorescent Equivalent	Lamp Shape	Base	ANSI Base
S9734	045923097348	120-277	14	25W-32W	T8	Medium Bi-Pin	G13

Lamp Code	Finish	MOL In Inches	MOD In Inches	Initial Lumens	Average Rated Hours	Kelvin Temp	Color
14T8/LED/48-830/DR	White	48"	1.00"	1800	50000	3000	Warm White

CRI	Beam Spread Deg	Pack	Package Type	RoHS Compliant	UL or ETL Listed	UL Classification	Warranty
82	230	10	Box	Yes	Yes	cETLus - Damp Location Rated	5 Year Limited
Status				Suggested Substitute			
Discontinued				S9934			



National Toll-Free:
800.43.SATCO
(800.437.2826)
www.satco.com

Distribution Centers:
New York, Florida, Texas,
Washington, California,
Puerto Rico

Corporate Offices:
110 Heartland Blvd.,
Brentwood, NY 11717
800.437.2826 631.243.2022
Fax 631.243.2027



©2012, Satco Products, Inc. Not responsible for typographical errors. 06/12 S1051