

STANDARD APPLIANCE ROCKERS



Fig. 1



Fig. 2



Fig. 3

Retail Part No.	Bulk Part No.	Figure No.	Circuit Function			Poles/Throws	AMPS 125VAC	AMPS 250VAC	Actuator Color	Actuator Material	Imprinting Color and Marking	Mounting Hole	Spec. Drawing Page No.
35-691	35-691-BU	1	On		Off	SPST	16	10	Black	Nylon		0.550" x 1.125"	H-23 A
35-694	35-694-BU	1	On	Off	On	SPDT	16	10	Black	Nylon		0.550" x 1.125"	H-23 B

Retail Part No.	Bulk Part No.	Figure No.	Circuit Function			Poles/Throws	AMPS 125VAC	AMPS 250VAC	HP 125/250VAC	Actuator Material	Imprinting Color and Marking	Mounting Hole	Spec. Drawing Page No.
35-3600	35-3600-BU	2	On		Off	SPST	15	10	3/4	Black Nylon		0.830" x 1.450"	H-23 C
35-3630	35-3630-BU	2	On		Off	DPST	15	10	3/4	Black Nylon		0.830" x 1.450"	H-23 D
35-3640	35-3640-BU	2	On		On	DPDT	15	10	3/4	Black Nylon		0.830" x 1.450"	H-23 E
35-3695	35-3695-BU	2	(On)	Off	(On)	DPDT	15	10	3/4	Black Nylon		0.830" x 1.450"	H-23 F
35-695	35-695-BU	3	(On)	Off	(On)	SPDT	16	16	1	Black Plastic		0.550" x 1.180"	H-23 G

Notes: (On) = Momentary On N/R = Not Rated † = 20A @ 277VAC and 2 H.P. @ 250VAC
 *3/4 H.P. @ 125/250VAC All of the Above have Quick Connect .250" Terminals

Note: All figures are for illustration purpose only, and the number/type of terminals may vary.

All quantities are single; BU's are packages of 25 Unless otherwise noted.

LIGHTED APPLIANCE ROCKERS



Fig. 4

On-Off Circuit Function

Retail Part No.	Bulk Part No.	Figure No.	Poles/Throws	AMPS 125VAC	AMPS 250VAC	HP 125 VAC	HP 250 VAC	HP 125-250 VAC	Actuator Color	Actuator Material	Lamp Voltage	Mounting Hole	Spec. Drawing Page No.
35-688	35-688-BU	5	SPST	15*	15	1/2	1		Lighted Red	Nylon	125V Ne	0.453" x 1.110"	H-23 H

Notes: *Built-in Resistor
 **Rated 10 Amps @ 30VDC
 ***Requires external resistor and diode for AC applications (not included)
 Incdt = Incandescent
 Ne = Neon
 N/R = Not Rated
 QC = Quick Connect

Note: All figures are for illustration purpose only, and the number/type of terminals may vary.

All quantities are single; BU's are packages of 25 Unless otherwise noted.